

# Keynote Speech

## Overview on Rotorcraft R&D in Japan

**Takashi Aoyama**

Chairperson

Japan Helicopter Society

Program Director of Aviation Technology

Aviation Technology Directorate

Japan Aerospace Exploration Agency (JAXA)

# Outline


- **Introduction of Japan Helicopter Society (JHS)**
- **Activities of Manufacturers**
  - Kawasaki Heavy Industries (KHI)
  - SUBARU
  - Mitsubishi Heavy Industries (MHI)
  - Yamaha Motor
  - Yamato Transport
- **Activities of Universities**
  - Nagoya University
  - Kanazawa Institute of Technology
  - Shizuoka Institute of Science and Technology
- **Activities of Research Institute**
  - Japan Aerospace Exploration Agency (JAXA)



日本ヘリコプタ協会  
Japan Helicopter Society

# Japan Helicopter Society (JHS)

- Established in 1989 with the aim of contributing to the community of helicopter and VTOL, from R&D, design, testing, manufacturing to operation
- Approved as the Japan Chapter of the American Helicopter Society (AHS) since its foundation and evaluated as one of the most active chapters outside U.S.
- Members: researchers, engineers, pilots, government officials, journalists, trading company workers, students...
- Main activities: Asian Rotorcraft Forum (ARF)/Heli Japan, Japan Helicopter Safety Team (JHST), publication of annual report, research meetings ...




# Kawasaki Heavy Industries



## Delivery of H145/BK117 D-3

- The latest version of BK117 codeveloped with Airbus Helicopters
- 5 bladed, GW=3.8ton, ducted fan, Rotor dia.=10.8m
- T/C by JCAB in 2021
- 14 aircraft had been ordered by the end of 2022 in Japan



CRM training

## CRM: Crew Resource Management

- CRM training services using a virtual reality (VR) simulator, intended to foster safer helicopter operations
- Training is intended to integrate not only the pilot, but also ground crew and other flight crew functioning in various capacities
- The goals include improving team communication, situational assessment skills and decision-making skills, which enable safer flight operations.



**SUBARU BELL 412EPX: Civil version**

# **SUBARU**

## **SUBARU BELL 412EPX**

- The latest version of BELL 412 codeveloped with BELL Helicopter
- T/C by FAA in 2018
- GW=5.5ton, Rotor dia.=14.02m
- 3 aircraft had been ordered by the end of 2022 in Japan



**UH-2: Military version**

## **UH-2 for Japan Ground Self Defense Force**

- In 2015, Ministry of Defense selected SUBARU BELL 412EPX as a platform of UH-2, the successor of UH-1J
- Maiden flight of mass production model and delivery started in 2022
- 26 aircraft were procured by the end of 2022
- Total 150 aircraft will be delivered by 2041

# Mitsubishi Heavy Industries



## Patrol helicopter XSH-60L

- New helicopter based on the SH-60K for the Japan Maritime Self Defense Force with improved on-board systems and flight performance
- Maiden flight and delivery of prototype in 2021



## CoasTitan™ Networked Security System with Uncrewed Vehicles

- Provides security solution with networked sensors and uncrewed aerial/surface/underwater vehicles
- UAV demonstrated its stable take off/landing capability on high-speed cruising ship in 2021



# Yamaha Motor

## FAZER R AP: New type of unmanned agricultural helicopter

- Automatic flight application “agFMS-IIH” installed to reduce workload for novice pilots to increase efficiency of pesticide/fertilizer spray operation

## YMR-II: New type of industrial use multirotor YMR series

- Sales start in 2023 spring, ¥1,859,000
- Automatic flight application “agFMS-IIH” installed
- GW=24.9kg, Size=L1,970mm W2,157mm H786mm

## FAZER R G2 with enhanced transportation capability

- Larger main rotor Dia.=3.115m ➡ 3.6m  
Payload 35kg ➡ 50kg
- For long distance automatic cargo transportation over unmanned area.




# Yamato Transport

## CycloRotors: mid-class cargo eVTOL

- Yamato Holdings Co., Ltd. + CycloTech GmbH (Austria) have successfully completed a joint feasibility study on applying a new thrust vectoring propulsion technology
- Key features for urban airborne logistic operations
  - = compact in size
  - + precision landing into confined areas (5 m in diameter)
  - + handling quality of challenging wind conditions
  - + transporting 45 kg payload over a distance of 40 km
- The unique characteristics of CycloRotors were used to design a mission optimized for unmanned cargo eVTOL.



# Nagoya University



## Stability derivative measurement of multirotor

- Stability characteristics of multirotor on hover conditions are studied analytically and experimentally.
- Especially,  $M_u$  and  $M_q$  are measured for analysis validation.
- $M_q$  is measured with respect to  $q$  as shown in figure.

## Vibration reduction by shifting c.g. position

- Analytical work by CAMRAD II demonstrated the effect without airframe instability.

## Methodology to design multirotor type flying car

- JAXA developed rFlow3D and rNoise are utilized with aerodynamic performance and noise as evaluation function.

## Aerodynamic interaction between rotor and wing when encountering crosswinds


- Studied by rFlow3D and wind tunnel test.

# Kanazawa Institute of Technology



## Aerodynamic interaction between rotor and wing

- Aerodynamic interaction of compound helicopter on hover and forward flight conditions are studied.
- Experimentally, 1m diameter radio-controlled helicopter with wing equipped with flaps is flight tested as shown in figure.
- It is shown that the flaps have favorable effect to reduce download during hover at the cost of diminishing roll damping.
- Analytical works are performed by JAXA developed rFlow3D.



## Flying wing (tailless fixed wing) type drone

- Prototyped, flight-tested and dynamic model formulated.
- Stable hover capability is demonstrated by flight test.
- Dynamic analysis shows wing aerodynamic effect becomes favorably dominant to static/dynamic stability along with velocity increase.

# Shizuoka Institute of Science and Technology



## Downwash prediction by LMT (Local Momentum Theory) on hover

- Effective inboard blade plan form of YAMAHA FAZER to generate engine cooling airflow is studied by LMT.
- Analysis by LMT and wind tunnel test result had excellent agreement.



## Optimization of multirotor arrangement by LMT


- Reducing aerodynamic interaction and airframe size is studied by LMT and validated by a test using rotors of YMR-08



## eVTOL prototyping


- Production design and prototyping for JAXA conceptual designed QTW
- Commercial “Pixhawk” is utilized for flight controller

# Organization of JAXA ATD



# JAXA: high-speed compound helicopter

## Technical challenges for high-speed compound helicopter




# JAXA: SAVERH

## SAVERH (Situation Awareness and Visual Enhancer for Rescue Helicopter)

- Guaranteeing low altitude mission under the DVE (Degraded Visual Environment).
- JAXA together with Shimadzu Co. has been conducting joint research project aiming at inventing method of presenting suitable information to the pilot to support search and rescue missions in DVE.
- An integrated system comprising an HMD (Helmet Mounted Display) and a variety of image sensors were installed in the JAXA research helicopter.



JAXA's Research Helicopter in night




# JAXA: D-NET

## Disaster Relief Aircraft Management System – Network



- Enables safe and efficient disaster response
- Connects helicopters and ground operation centers/ headquarters
- Enables information sharing
  - Flight plans
  - Telemetry data (positions)
  - Disaster mission type (rescue, reconnaissance, etc.)



## Adopted by the Japan Disaster Relief Agencies

- D-NET is adopted by most disaster relief agencies in Japan.
- D-NET enables intra-agency information sharing which contributes to efficient large-scale disaster response

# Unstructured Based CFD Solver for Rotorcraft and its Applications

- JAXA has been devoted to developing a fast CFD solver, FaSTAR-Move (Fast Aerodynamic Routine-Move) in order to be applied complex shaped moving objects according to industrial needs.
- Recently, several rotorcraft simulations have been performed using FaSTAR-Move.

